

LED LIGHTS

PHOTO	ITEM	PART #	NOTES	PRICE	DESCRIPTION
	4.5" 25 Watt Cree Light Cannon	4.5can25wc	Pair of 4 1/2" 25 Watt Cree LED includes harness and amber lenses	\$373.99	•1000' of Usable Light • 25 Watt Cree Single LED for Smoothest Pattern • 4.5" Round with 10 Degree Narrow Beam. Optional Snap on Filters • Universal Single Bolt Mounting • Ultra Lightweight 2lb Hybrid Construction • Proprietary IRIS Reflector
	4.5" 25 Watt Luminus LED Light Cannon	4.5can25wl	Pair of 4 1/2" 25 Watt Luminus LED includes harness and amber lenses cover	\$499.99	•1000' of Usable Light Bulb - LUMNIUS 25W Voltage 9-32V Rated Power 25W Brightness 1800Lm Housing Aluminum Back + Nylon Front Lens Polycarbonate / PC Bracket Stainless Steel Connector Detuch Size 125*120*150MM Cover Ambr Connector Detuch
	6.7" 65 Watt Cree Light Cannon	6.7can65wc	Pair of 6 3/4" 65 Watt Cree LED includes harness and amber lenses cover	\$999.99	Bulb Cree 65W Voltage 9-32V Rated Power 65W Brightness 3800Lm Housing Aluminum Back + Nylon Front Lens Polycarbonate / PC Bracket Stainless Steel Connector Detuch Size 230*181*175MM
	6.7" 65 Watt Luminus LED Light Cannon	6.7can65wl	Pair of 6 3/4" 65 Watt Luminus LED includes harness and amber lenses cover	\$1124.99	Bulb LUMNIUS 65W Voltage 9-32V Rated Power 65W Brightness 3800Lm Housing Aluminum Back + Nylon Front Lens Polycarbonate / PC Bracket Stainless Steel Connector Detuch Size 230*181*175MM
	9 Inch HID DRIVING LIGHT 75 WATTS	9HID75SPOT	9 " 75w 10-30v led work light (spot)	\$162.49	Operational Wattage: 75W Rated output power: 75w+/-3w Rated operating voltage:9-18v DC Output voltage: 85v +/-17v Lens: PMMA Poly (menthyl methacrylate) Material: Plastic Housing: High Impact ABS Reflector: Die-cast Aluminum Ballast: H3/6000K Xenon Bulb Hid Bulb Life Time: over 2500 hours Size: 9inch Theoretical Lumens Output: 4900LM Operating Lumens Output: 4100LM Current draw: 4.6A @ 12V Operation temperature -40°C ~ 80°C Unit Dimensions: 10 inches x 11 inches x 7 inches Unit weight: 4 pounds (without box)
	9 Inch HID DRIVING LIGHT 100 WATTS	9HID100SPOT	9 " 100w 10-30v led work light (spot)	\$187.49	Operational Wattage: 100W Rated output power: 100w+/-3w Rated operating voltage:9-18v DC Output voltage: 85v +/-17v Lens: PMMA Poly (menthyl methacrylate) Material: Plastic Housing: High Impact ABS Reflector: Die-cast Aluminum Ballast: H3/6000K Xenon Bulb Hid Bulb Life Time: over 2500 hours Size: 9inch Theoretical Lumens Output: 4900LM Operating Lumens Output: 4100LM Current draw: 4.6A @ 12V Operation temperature -40°C ~ 80°C Unit Dimensions: 10 inches x 11 inches x 7 inches Unit weight: 4 pounds (without box)
	9 Inch HID DRIVING LIGHT 75 WATTS	9HID75FLOOD	9 " 75w 10-30v led work light flood	\$162.49	Operational Wattage: 75W Rated output power: 75w+/-3w Rated operating voltage:9-18v DC Output voltage: 85v +/-17v Lens: PMMA Poly (menthyl methacrylate) Material: Plastic Housing: High Impact ABS Reflector: Die-cast Aluminum Ballast: H3/6000K Xenon Bulb Hid Bulb Life Time: over 2500 hours Size: 9inch Theoretical Lumens Output: 4900LM Operating Lumens Output: 4100LM Current draw: 4.6A @ 12V Operation temperature -40°C ~ 80°C Unit Dimensions: 10 inches x 11 inches x 7 inches Unit weight: 4 pounds (without box)
	9 Inch HID DRIVING LIGHT 100 WATTS	9HID100FLOOD	9 " 100w 10-30v led work light flood	\$187.49	Operational Wattage: 100W Rated output power: 100w+/-3w Rated operating voltage:9-18v DC Output voltage: 85v +/-17v Lens: PMMA Poly (menthyl methacrylate) Material: Plastic Housing: High Impact ABS Reflector: Die-cast Aluminum Ballast: H3/6000K Xenon Bulb Hid Bulb Life Time: over 2500 hours Size: 9inch Theoretical Lumens Output: 4900LM Operating Lumens Output: 4100LM Current draw: 4.6A @ 12V Operation temperature -40°C ~ 80°C Unit Dimensions: 10 inches x 11 inches x 7 inches Unit weight: 4 pounds (without box)
	4.2 Inch LED WORK LIGHT 25 WATTS	425LEDWORK	25w cree led work light	\$162.49	. LED Power: 25W . Operating Voltage: 10-60V DC . Waterproof rate: IP 67 . 25pcs*1w high intensity CREE LEDs . Optional Color: Black,White . Color Temperature: 6500K . Material:Diecast aluminum housing . Lens material:PMMA . Mounting Bracket: Stainless Steel . Opitonal Beam: 60 / 15 degree . 30000 hours above life time . Size:4.0inch . 106mm*106mm*70mm Certificates:CE, RoHS, IP67
	6 Inch LED LIGHT BAR 60 WATTS	660LEDBAR	10-60V led work light 60W cree	\$237.49	. LED Power: 60W . Operating Voltage: 10-30V DC . Waterproof rate: IP 67 . 6pcs*10w high intensity CREE LEDs . Optional Color: Black,White . Color Temperature:6000K . Material:Diecast aluminum housing . Lens material:PC . Mounting Bracket: Stainless Steel . Opitonal Beam: Spot/Flood . 30000 hours above life time . Size: 5.2inch . 135mm*124mm*120mm . Certificates:CE, RoHS, IP67
	7 Inch LED LIGHT BAR 90 WATTS	SP-4402	10-60V led work light 90W cree	\$274.99	. LED Power: 90W . Operating Voltage: 10-30V DC . Waterproof rate: IP 67 . 9pcs*10w high intensity CREE LEDs . Optional Color: Black,White . Color Temperature:6000K . Material:Diecast aluminum housing . Lens material:PC . Mounting Bracket: Stainless Steel . Opitonal Beam: 10 degree . 30000 hours above life time . Dimensions: 5.2 inch . Certificates:CE, RoHS, IP67
	5 Inch LED BUMPER MOUNT 12 WATTS	SP-414312W	BUMPER MOUNT 4 LED FLOOD	\$124.99	. LED Power: 12W . Operating Voltage: 10-30V DC . Waterproof rate: IP 67 . 4pcs*3w high intensity CREE LEDs . Optional Color: Black,White . Color Temperature: 6000K . Material:Diecast aluminum housing . Lens material:PMMA . Mounting Bracket: Stainless Steel . Opitonal Beam: 8 / 90 degree beam . 30000 hours above life time . Dimensions: 3.0 inch Certificates:CE, RoHS, IP67
	6 Inch LED BUMPER MOUNT 18 WATTS	SP-414418W	BUMPER MOUNT 6 LED FLOOD	\$149.99	. LED Power: 18W . Operating Voltage: 10-30V DC . Waterproof rate: IP 67 . 6pcs*3w high intensity CREE LEDs . Optional Color: Black,White . Color Temperature: 6000K . Material:Diecast aluminum housing . Lens material:PMMA . Mounting Bracket: Stainless Steel . Opitonal Beam: 8 / 90 degree beam . 30000 hours above life time . Dimensions: 3.0 inch Certificates:CE, RoHS, IP67
	11 Inch LED LIGHT BAR 120 WATTS	11120LEDBAR	cree led light bar 120w	\$349.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC . Housing color: Black
	17 Inch LED LIGHT BAR 200 WATTS	17200LEDBAR	cree led light bar 200w	\$524.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC . Housing color: Black
	20 Inch LED LIGHT BAR 240 WATTS	20240LEDBAR	cree led light bar 240w	\$599.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC . Housing color: Black
	33 Inch LED LIGHT BAR 180 WATTS	4017180BAR	cree led light bar 180w	\$574.99	. CREE LED Each 10W/PC . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam:spot beam, flood beam and combo beam . Material: Diecast aluminum housing . LENS: toughened glass . Housing color: Black . About 50000 hours life time
	38 Inch LED LIGHT BAR 210 WATTS	4017210BAR	cree led light bar 210w	\$624.99	. CREE LED Each 10W/PC . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam:spot beam, flood beam and combo beam . Material: Diecast aluminum housing . LENS: toughened glass . Housing color: Black . About 50000 hours life time
	17 Inch LED LIGHT BAR 100 WATTS	21100LEDBAR	10pcs*10w CREE LEDs 100 watts Beam: 8 "Spot/90" flood/Combo 21.5"	\$362.49	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: SpotMaterial: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	22 Inch LED LIGHT BAR 120 WATTS	22120LEDBAR	120WATT 40 piece *3w Epsitar leds Beam:12" Spot/ 60" flood/Combo	\$337.49	. 3w Epstar leds. Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	50 Inch LED LIGHT BAR 288 WATTS	50288LEDBAR	96pcs*3w CREE LEDs 50" 288 watts	\$587.49	. 3w each Cree LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP65 . Beam: Spot beam, flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Alu firm bracket . LENS: PC . About 20000 hours life time
	50 Inch Led Light Bar 304 Watts	SP2X4018-304W	WL8018-304W led light bar	\$749.99	. CREE LED Each 3W/PC (beside),CREE LED Each 10W/PC(Middle) . Operating Volt: 9-32Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: 60" flood beam, 25"spot beam(beside),10"spot beam (middle) . Material: Diecast aluminum housing . LENS: PC . Housing color: Black . About 30000 hours life time
	22 Inch Curved Led Light Bar	SP2240-120W	120w led light bar	\$349.99	. 3W each CREE LED . Operating Volt: 9-32Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: 60" flood beam, 30"spot beam,combo . Material: Diecast aluminum housing . LENS: unbreakable PC . Housing color: Black . About 30,000 hours life time
	33 Inch Curved Led Light Bar	SP3360-180W	180w led light bar	\$399.99	. 3W each CREE LED . Operating Volt: 9-32Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: 60" flood beam, 30"spot beam,combo . Material: Diecast aluminum housing . LENS: unbreakable PC . Housing color: Black . About 30,000 hours life time
	42 Inch Curved Led Light Bar	SP4280-240W	240w led light bar	\$499.99	. 3W each CREE LED . Operating Volt: 9-32Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: 60" flood beam, 30"spot beam,combo . Material: Diecast aluminum housing . LENS: unbreakable PC . Housing color: Black . About 30,000 hours life time
	50 Inch Curved Led Light Bar	SP5096-288W	288w led light bar	\$782.49	. 3W each CREE LED . Operating Volt: 9-32Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: 60" flood beam, 30"spot beam,combo . Material: Diecast aluminum housing . LENS: unbreakable PC . Housing color: Black . About 30,000 hours life time
	52 Inch Curved Led Light Bar	SP52100-300W	300w led light bar	\$749.99	. 3W each CREE LED . Operating Volt: 9-32Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: 60" flood beam, 30"spot beam,combo . Material: Diecast aluminum housing . LENS: unbreakable PC . Housing color: Black . About 30,000 hours life time
	20 Inch LED LIGHT BAR 60 WATTS	SP2X4013-60W	60w 20 "	\$374.99	. 5W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam . Material: Diecast aluminum housing . Mounting Bracket: Zinc alloy . LENS: PC . Housing color: Black
	30 Inch LED LIGHT BAR 90 WATTS	SP2X4013-90W	90w 30 "	\$499.99	. 5W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam . Material: Diecast aluminum housing . Mounting Bracket: Zinc alloy . LENS: PC . Housing color: Black
	40 Inch LED LIGHT BAR 120 WATTS	SP2X4013-120W	120w 40 "	\$624.99	. 5W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam . Material: Diecast aluminum housing . Mounting Bracket: Zinc alloy . LENS: PC . Housing color: Black
	5 Inch Led Light Bar	SP2X4012-5X20-2OWS	20w led light bar	\$99.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC . Housing color: Black
	5 Inch Led Light Bar	SP2X4012-5X20-2OWF	20w led light bar	\$99.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	8 Inch Led Light Bar	SP2X4012-8X40-4OWS	40w led light bar	\$149.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	8 Inch Led Light Bar	SP2X4012-8X40-4OWF	40w led light bar	\$149.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	11 Inch LED LIGHT BAR 60 WATTS	sp2x4012-11x60-60w	60w led light bar	\$187.49	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC . Housing color: Black
	17 Inch LED LIGHT BAR 100 WATTS	sp2x4012-17x100-100w	100w led light bar	\$337.49	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	20 Inch LED LIGHT BAR 120 WATTS	sp2x4012-20x120-120w	120w led light bar	\$412.49	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	30 Inch LED LIGHT BAR 180 WATTS	sp2x4012-30x180-180w	180w led light bar	\$537.49	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	39 Inch LED LIGHT BAR 240 WATTS	sp2x4012-39x240-240w	240w led light bar	\$599.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC . Housing color: Black
	42 Inch LED LIGHT BAR 260 WATTS	sp2x4012-42x260-260w	260w led light bar	\$662.49	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	50 Inch LED LIGHT BAR 300 WATTS	sp2x4012-50x300-300w	300w led light bar	\$749.99	. 10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	50 Inch Curved LED LIGHT BAR 240 WATTS	sp2x4012-50curved-240	240w Curved led light bar	\$874.99	10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	52 Inch Curved LED LIGHT BAR 264 WATTS	sp2x4031curved-264w	264w curved led bar	\$924.99	10W each CREE LED . Operating Volt: 10-60Volt DC . Color temperature: 5000K, 6500K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam, flood beam,combo beam . Material: Diecast aluminum housing . Mounting Bracket: Aluminum alloy with stainless steel bracket . LENS: PC .
	4 Inch led light bar	418WL8024	4 "18W	\$87.49	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	6.5 Inch led light bar	6.536WL8024	6.5 "36W	\$112.49	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	9 Inch led light bar	954WL8024	9 "54W	\$124.99	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	12 Inch led light bar	1272WL8024	12 " 72W	\$149.99	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	14.5 Inch led light bar	14.590WL8024	14.5 " 90W	\$162.49	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	18 Inch led light bar	18108WL8024	18 " 108W	\$187.49	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	22 Inch led light bar	22126WL8024	22 " 126W	\$212.49	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	24 Inch led light bar	24144WL8024	24 " 144W	\$237.49	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	28 Inch led light bar	28180WL8024	28 " 180W	\$274.99	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	36 Inch led light bar	36234WL8024	36 "234W	\$374.99	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	40 Inch led light bar	40270WL8024	40 "270W	\$412.49	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time
	45 Inch led light bar	45288WL8024	45"288W	\$499.99	. 3W each CREE LED . Operating Volt: 10-30Volt DC . Color temperature: 6000K . Operation temperature -40°C-60°C . Waterproof rate: IP67 . Beam: Spot beam,flood beam, combo beam . Material: Diecast aluminum housing . Mounting Bracket: Stainless steel bracket . LENS: PC LENS . About 50000 hours life time